



TH13WS3-01


MODULAR




TH13WS5-04



TH13WS4-02



TH13WS1-05



TH13WS2-03

Thistle

Specification


Product Name	Thistle
Pile Construction	Texture Multi-Level Loop
Tufted Yarn Weight	520g/m ²
Face Yarn Type	100% Bulk Continuous Filament Fiber
Dye Method	100% Solution Dyed
Machine Gauge	1/12
Primary Backing	Polyester Premium Fabric
Secondary Backing	PVC with Fibreglass
Pile Thickness	3.5mm ± 0.5
Total Thickness	5.5mm ± 0.5
Tile Size	50cm x 50cm

Performance Test

Flammability	Pass GB 8624-2006 Pass GB/T 14768-93
Smoke Density	Pass ASTM E-662 ≤450 DMC Pass GB 8624-2006
Static Generation	Pass AATCC-134 Pass GB/T 18044-2000
Colourfastness to Water	Pass AATCC-16E Pass Grade 4/5 ISO 105-X12 Pass BS EN ISO 105 E01:1996
Colourfastness to Light	Pass AATCC-16E Pass Grade 5 ISO B02:1994E Pass BS EN ISO 105 B02:1999
Colourfastness to Crocking	Pass BS EN ISO 105-X12:2002
Tensile Strength Test	Pass ISO 13934-1 Warp 3112.9

Disclaimer


- This carpet is manufactured and sold for floorcovering use only.
- As with all carpets, colours are subject to dye lot variations.
- All carpet specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice.
- "Tufted Pile Weight" refers to total input weight of yarn used in tufting process, and processes such as tufting, shearing and carving will result in a lower finished yarn weight in purchased carpets.




TH13WS3-01




TH13WS4-02



TH13WS2-03




TH13WS5-04



TH13WS1-05



MODULAR



MODULAR

malaysia

Thistle



Thistle